

**SAFETY DATA SHEET**  
FUEL CLEAN GASOLINE

Page: 1

Compilation date: 11-02-2015

Revision No: 1

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** FUEL CLEAN GASOLINE

**Product code:** 2031

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** Cleaner fuel systems.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** ProPart International B.V.

Molenakker 3

Reuver

5953 TW

The Netherlands

**Tel:** +31 (0) 77 476 2368

**Fax:** +31 (0) 77 476 2424

**Email:** [info@propart-international.com](mailto:info@propart-international.com)

**1.4. Emergency telephone number**

**Emergency tel:** +31 (0) 77 476 2368 (08.30-17.00)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Asp. Tox. 1: H304; Acute Tox. 3: H331; Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; Flam. Liq. 3: H226; -: EUH066; -: EUH210; -: EUH401

**Most important adverse effects:** Flammable liquid and vapour. May be fatal if swallowed and enters airways. Toxic if inhaled. Highly flammable liquid and vapour. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. Safety data sheet available on request. To avoid risks to human health and the environment, comply with the instructions for use.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H331: Toxic if inhaled.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

[cont...]

# SAFETY DATA SHEET

## FUEL CLEAN GASOLINE

Page: 2

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH210: Safety data sheet available on request.

EUH401: To avoid risks to human health and the environment, comply with the instructions for use.

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame



**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233: Keep container tightly closed.  
P240: Ground/Bond container and receiving equipment.  
P241: Use explosion-proof electrical/ventilating/lighting equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.  
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P311: Call a POISON CENTER/doctor/.  
P331: Do NOT induce vomiting.  
P403+233: Store in a well-ventilated place. Keep container tightly closed.  
P235: Keep cool.  
P405: Store locked up.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

[cont...]

# SAFETY DATA SHEET

FUEL CLEAN GASOLINE

Page: 3

## Hazardous ingredients:

PROPAN-2-OL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	35.000%

## Non-classified ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

EINECS	CAS	CHIP Classification	CLP Classification	Percent
265-150-3	64742-48-9	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226	65.000%

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Do not use solvents or thinners. Repeated exposure may result in a non allergic eczema.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Consult a doctor. Keep person warm and at rest. Do not induce vomiting.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Inhalation of mist may cause irritations to the respiratory tract. Excessive exposure may cause dizziness and nausea. Move to fresh air in case of accidental inhalation of vapours. When symptoms persist consult doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact. Repeated or prolonged exposure to the product can result in a non allergic contact eczema. Short-term contacts are harmless.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Dry chemical powder. Carbon dioxide. Water fog. Use water spray to cool containers. Do not use water jet.

[cont...]

# SAFETY DATA SHEET

## FUEL CLEAN GASOLINE

Page: 4

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. Collect extinguishing water to prevent it from draining into the sewer system.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks. Clean preferably with a detergent, do not use solvent.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS. Refer to section 13 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools. Preventive skin protection by using skin protection cream. Do not eat, drink or smoke when using this product. Workers should wash hands and face before eating, drinking and smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep away from direct sunlight. Keep away from sources of ignition. Keep container tightly closed. Ensure lighting and electrical equipment are not a source of ignition. Do not store together with food. Do not store together with acids. Do not store together with bases.

[cont...]

# SAFETY DATA SHEET

FUEL CLEAN GASOLINE

Page: 5

## 7.3. Specific end use(s)

**Specific end use(s):** Do not mix with other greases.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**PROPAN-2-OL**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	999 mg/m <sup>3</sup>	1250 mg/m <sup>3</sup>	-	-

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency. In case of insufficient ventilation wear respiratory protection.

**Hand protection:** Protective gloves. After repeated contact possible to apply a skin barrier cream. Do not use when contact has already been.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Protective clothing. After contact clean all parts of the body that came in contact with the product.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Brown

**Odour:** Characteristic odour

**Solubility in water:** Partially soluble.

**Flammability limits %:** lower: 1

**upper:** 12

**Flash point°C:** <23

**Autoflammability°C:** No data available.

**Vapour pressure:** No data available.

### 9.2. Other information

**Other information:** Density: appr. 0,8 (20°C). Mixing ratio: 250ml to 50 liters of fuel.

## Section 10: Stability and reactivity

[cont...]

# SAFETY DATA SHEET

FUEL CLEAN GASOLINE

Page: 6

## 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

## 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

## 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

## 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

## 10.5. Incompatible materials

**Materials to avoid:** Oxidising agents. Strong bases. Strong acids.

## 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide. Smoke.  
Decomposition products such as aldehydes and ketones.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

**Relevant hazards for substance:**

Hazard	Route	Basis
Acute toxicity (ac. tox. 3)	INH	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact. Repeated or prolonged exposure to the product can result in a non allergic contact eczema. Short-term contacts are harmless.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

[cont...]

# SAFETY DATA SHEET

FUEL CLEAN GASOLINE

Page: 7

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Not biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** No data available.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company. Must not be disposed together with household garbage or into the sewage system.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1993

### 14.2. UN proper shipping name

**Shipping name:** FLAMMABLE LIQUID, N.O.S.  
(LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM),  
HYDROTREATED HEAVY)

### 14.3. Transport hazard class(es)

**Transport class:** 3

### 14.4. Packing group

**Packing group:** III

[cont...]

# SAFETY DATA SHEET

FUEL CLEAN GASOLINE

Page: 8

## 14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Regulation (EC) No. 1907/2006.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

EUH210: Safety data sheet available on request.

EUH401: To avoid risks to human health and the environment, comply with the instructions for use.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.