

2K Rapido (50ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
 Date of issue: 2/3/2020 Revision date: 2/3/2020 Supersedes: 2/3/2020 Version: 3.4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : 2K Rapido (50ml)
 Product code : 7120
 Type of product : Adhesives, sealants

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
 Use of the substance/mixture : 2K Rapido is a fast curing and slightly expanding 2-component injection material that can be used for a wide variety of assembly work in the construction and maintenance sector (eg drilled holes)

1.2.2. Uses advised against

Restrictions on use : No additional information available

1.3. Details of the supplier of the safety data sheet

ProPart International
 Molenakker 3
 5953 TW Reuver - Nederland
 T +31 (0) 77 476 2204
info@propart-international.com - www.propart-international.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (inhal.), Category 4 H332
 Skin corrosion/irritation, Category 2 H315
 Serious eye damage/eye irritation, Category 2 H319
 Respiratory sensitisation, Category 1 H334
 Skin sensitisation, Category 1 H317
 Carcinogenicity, Category 2 H351
 Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335
 Specific target organ toxicity — Repeated exposure, Category 2 H373
 Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No information available.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS08

Signal word (CLP) : Danger

Hazardous ingredients : DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES); 4,4'-METHYLENEDIPHENYL DIISOCYANATE, OLIGOMERS; Polyisocyanate prepolymer based on MDI

2K Rapido (50ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard statements (CLP)	: H315 - Causes skin irritation. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H332 - Harmful if inhaled. H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 - May cause respiratory irritation. H351 - Suspected of causing cancer. H373 - May cause damage to organs through prolonged or repeated exposure.
Precautionary statements (CLP)	: P260 - Do not breathe vapours. P308+P311 - IF exposed or concerned: Call a POISON CENTER, a doctor. P280 - Wear protective gloves, protective clothing, eye protection. P302+P352 - IF ON SKIN: Wash with plenty of water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P285 In case of inadequate ventilation wear respiratory protection.
EUH-statements	: EUH204 - Contains isocyanates. May produce an allergic reaction.
UFI	: 59QM-80UF-H00J-GEFH

2.3. Other hazards

Other hazards not contributing to the classification : Polymerisation can occur. May release heat.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethylenediamine, propoxylated	(CAS-No.) 25214-63-5 (EC-No.) 500-035-6	10 - 20	Eye Irrit. 2, H319
DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)	(CAS-No.) 9016-87-9 (EC-No.) 618-498-9 (EC Index-No.) 615-005-01-6	10 - 20	Carc. 2, H351 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317
4,4'-METHYLENEDIPHENYL DIISOCYANATE, OLIGOMERS	(CAS-No.) 25686-28-6 (EC-No.) 500-040-3 (REACH-no) 01-2119457013-49	10 - 20	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
Polyisocyanate prepolymer based on MDI		10 - 20	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
2-methylpentane-1,5-diamine	(CAS-No.) 15520-10-2 (EC-No.) 239-556-6	< 1	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Keep under medical supervision for at least 48 hours.

2K Rapido (50ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. Rinse with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Drink plenty of water. Call a POISON CENTER/doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause sensitization by inhalation. Respiratory tract irritation. Respiratory sensitization. Inhalation may cause asthmatic reactions. Inhalation may cause irritation (cough, short breathing, difficulty in breathing). Dyspnoea. Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Below limit. Inhalation of vapour or fumes can cause severe breath difficulties.
Symptoms/effects after skin contact	: Irritating to the skin and mucous membranes. Burns.
Symptoms/effects after eye contact	: Eye irritation. Burns.
Symptoms/effects after ingestion	: Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

"Sensitising:" waste which contains one or more substances known to cause sensitising effects to the skin or the respiratory organs. Respiratory system diseases. May cause burns.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Carbon dioxide. Dry powder. If there is a fire close by, use suitable extinguishing agents. Alcohol-resistant foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: May release heat. Polymerisation risk.
Reactivity in case of fire	: Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide. Small amounts: Nitrous fumes. Hydrogen cyanide. Isocyanate Vapors.

5.3. Advice for firefighters

Firefighting instructions	: Prevent fire fighting water from entering the environment. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use protective clothing.
------------------	----------------------------

6.1.1. For non-emergency personnel

Protective equipment	: Refer to protective measures listed in Sections 7 and 8.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Cover with moist, liquid-binding material (eg sand, binder for chemicals based on calcium silicate hydrate). Take up mechanically after 1 hour and put in waste packaging, do not close (CO ₂ development). Keep moist and leave it in a safe place in the open air for 7 to 14 days. This material and its container must be disposed of in a safe way, and as per local legislation.
Other information	: Ensure adequate air ventilation.

6.4. Reference to other sections

Stable under recommended handling and storage conditions (see section 7). Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Do not eat, drink or smoke when using this product. Use personal protective equipment as required. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

2K Rapido (50ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: The floor of the depot should be impermeable and designed to form a water-tight basin.
Storage conditions	: Store in original container. Keep container tightly closed. Keep cool.
Special rules on packaging	: Keep container tightly closed and dry. Keep in a cool place. Keep only in original container.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2K Rapido (50ml)

DNEL/DMEL (Workers)

Acute - systemic effects, dermal	≈ mg/kg bodyweight/day
----------------------------------	------------------------

Ethylenediamine, propoxylated (25214-63-5)

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	13.9 mg/kg bodyweight/day
--------------------------------------	---------------------------

Long-term - systemic effects, inhalation	98 mg/m ³
--	----------------------

DNEL/DMEL (General population)

Long-term - systemic effects, oral	8.3 mg/kg bodyweight/day
------------------------------------	--------------------------

Long-term - systemic effects, inhalation	29 mg/m ³
--	----------------------

Long-term - systemic effects, dermal	8.3 mg/kg bodyweight/day
--------------------------------------	--------------------------

PNEC (Water)

PNEC aqua (freshwater)	0.085 mg/l
------------------------	------------

PNEC aqua (marine water)	0.0085 mg/l
--------------------------	-------------

PNEC aqua (intermittent, freshwater)	1.51 mg/l
--------------------------------------	-----------

PNEC (Sediment)

PNEC sediment (freshwater)	0.193 mg/kg dwt
----------------------------	-----------------

PNEC sediment (marine water)	0.0193 mg/kg dwt
------------------------------	------------------

PNEC (Soil)

PNEC soil	0.0183 mg/kg dwt
-----------	------------------

PNEC (STP)

PNEC sewage treatment plant	70 mg/l
-----------------------------	---------

4,4'-METHYLENEDIPHENYL DIISOCYANATE, OLIGOMERS (25686-28-6)

DNEL/DMEL (Workers)

Acute - systemic effects, dermal	50 mg/kg bodyweight/day
----------------------------------	-------------------------

Acute - systemic effects, inhalation	0.1 mg/m ³
--------------------------------------	-----------------------

Acute - local effects, dermal	28.7 mg/cm ²
-------------------------------	-------------------------

Acute - local effects, inhalation	0.1 mg/m ³
-----------------------------------	-----------------------

Long-term - systemic effects, inhalation	0.05 mg/m ³
--	------------------------

Long-term - local effects, inhalation	0.05 mg/m ³
---------------------------------------	------------------------

DNEL/DMEL (General population)

Acute - systemic effects, inhalation	0.05 mg/m ³
--------------------------------------	------------------------

Acute - local effects, inhalation	0.05 mg/m ³
-----------------------------------	------------------------

Long-term - systemic effects, oral	20 mg/kg bodyweight/day
------------------------------------	-------------------------

Long-term - systemic effects, inhalation	0.025 mg/m ³
--	-------------------------

Long-term - systemic effects, dermal	25 mg/kg bodyweight/day
--------------------------------------	-------------------------

Long-term - local effects, dermal	17.2 mg/kg bw/day
-----------------------------------	-------------------

Long-term - local effects, inhalation	0.025 mg/m ³
---------------------------------------	-------------------------

2K Rapido (50ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4,4'-METHYLENEDIPHENYL DIISOCYANATE, OLIGOMERS (25686-28-6)

PNEC (Water)

PNEC aqua (freshwater)	1 mg/l
PNEC aqua (marine water)	0.1 mg/l
PNEC aqua (intermittent, freshwater)	10 mg/l

PNEC (Soil)

PNEC soil	1 mg/kg dwt
-----------	-------------

PNEC (STP)

PNEC sewage treatment plant	1 mg/l
-----------------------------	--------

2-methylpentane-1,5-diamine (15520-10-2)

DNEL/DMEL (Workers)

Acute - local effects, inhalation	0.5 mg/m ³
Long-term - systemic effects, dermal	1.5 mg/kg bodyweight/day
Long-term - local effects, inhalation	0.25 mg/m ³

DNEL/DMEL (General population)

Acute - local effects, inhalation	0.25 mg/m ³
Long-term - systemic effects, oral	0.75 mg/kg bodyweight/day
Long-term - systemic effects, dermal	0.75 mg/kg bodyweight/day
Long-term - local effects, inhalation	0.125 mg/m ³

PNEC (Water)

PNEC aqua (freshwater)	0.42 mg/l
PNEC aqua (marine water)	0.042 mg/l
PNEC aqua (intermittent, freshwater)	0.42 mg/l

PNEC (Sediment)

PNEC sediment (freshwater)	7.58 mg/kg dwt
PNEC sediment (marine water)	0.758 mg/kg dwt

PNEC (Soil)

PNEC soil	1.27 mg/kg dwt
-----------	----------------

PNEC (STP)

PNEC sewage treatment plant	1.25 g/l
-----------------------------	----------

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

In case of inadequate ventilation wear respiratory protection. Gloves. Safety glasses.

Materials for protective clothing:

Use personal protective equipment as required. Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment. Body protection. Tyvek® Gown/Coveralls. Pro-Tech 'C'. Pro Tech 'F'. (preferably thick cotton). Fully protective clothing for single use.

Hand protection:

Chemical resistant gloves (according to European standard EN 374 or equivalent). Wear suitable gloves resistant to chemical penetration, and microorganisms. Butyl-rubber protective gloves. Neoprene/viton®. Chlorinated polyethylene. Chemical resistant PVC gloves (to European standard EN 374 or equivalent)

2K Rapido (50ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
By prolonged exposure : Protective gloves	Butyl rubber, Neoprene rubber (HNBR), Viton® II, Chlorinated polyethylene, Polyvinylchloride (PVC)	5 (> 240 minutes)			EN ISO 374
short term, Protective gloves	Chlorinated polyethylene, Nitrile rubber (NBR)	3 (> 60 minutes)			EN ISO 374

Eye protection:

Wear security glasses which protect from splashes

Respiratory protection:

Air-fed respiratory protective equipment should be worn when this product is sprayed if the exposure of the sprayer or other people nearby cannot be controlled to below the occupational exposure limit. If this material is handled in other than in a closed system, approved supplied air respirator operated in a positive pressure mode is recommended. Respirators with air supply and flight cylinder are recommended when the oxygen concentrations are insufficient, the gas / vapor warning data are limited, or when the air filter capacity / degree can be exceeded.

Device	Filter type	Condition	Standard
Half-face mask (DIN EN 140)	Gas filters, Type B - Inorganic gases (hydrogen sulfide, chlorine, hydrogen cyanide), Filtering Half-face mask (DIN EN 149), EN 143		EN 136, EN 140, EN 405

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: Polymerization
Flash point	: Polymerization
Auto-ignition temperature	: Polymerization
Decomposition temperature	: Polymerization
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.5
Solubility	: Water: Insoluble
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 0 g/l
-------------	---------

2K Rapido (50ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

Poisonous nitrous gasses may form in case of fire. On burning: release of carbon monoxide - carbon dioxide. Isocyanate Vapors. Hydrogen cyanide.

10.2. Chemical stability

Hardening time : 10-15

10.3. Possibility of hazardous reactions

Polymerization. May release heat.

10.4. Conditions to avoid

Stable in use and storage conditions as recommended in item 7.

10.5. Incompatible materials

The product reacts slowly with water resulting in evolution of carbon dioxide. Container can be pressurised by carbon dioxide due to reaction with humid air and/or water. pressure rise and possible bursting of container. Risk of explosion upon a rise of pressure.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. Nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Harmful if inhaled.

Ethylenediamine, propoxylated (25214-63-5)

LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg

4,4'-METHYLENEDIPHENYL DIISOCYANATE, OLIGOMERS (25686-28-6)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 9400 mg/kg
LC50 inhalation rat (mg/l)	2.24 mg/l (1h)

2-methylpentane-1,5-diamine (15520-10-2)

LD50 oral rat	1690 mg/kg
LD50 dermal rat	1870 mg/kg
LC50 inhalation rat (ppm)	4.9 ppm/1h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer.
Reproductive toxicity : Not classified
STOT-single exposure : May cause respiratory irritation.
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

Ethylenediamine, propoxylated (25214-63-5)

LC50 fish 1	≈ 4600 mg/l Test organisms (species): Leuciscus idus
EC50 Daphnia 1	> 100 mg/l

2K Rapido (50ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 72h algae (1)	150.67 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
--------------------	--

4,4'-METHYLENEDIPHENYL DIISOCYANATE, OLIGOMERS (25686-28-6)

EC50 Daphnia 1	129.7 mg/l (24h OECD 202)
ErC50 (algae)	> 16400 mg/l (72h OECD 201)
NOEC (chronic)	>= 10 mg/l (21d Daphnia magna OECD211)

2-methylpentane-1,5-diamine (15520-10-2)

LC50 fish 1	130 mg/l (48h OECD 203)
EC50 Daphnia 1	50 mg/l
EC50 72h algae (1)	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

2K Rapido (50ml)

Persistence and degradability	No additional information available.
-------------------------------	--------------------------------------

12.3. Bioaccumulative potential

2K Rapido (50ml)

Bioaccumulative potential	No additional information available.
---------------------------	--------------------------------------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Do not dispose of with domestic waste. Avoid release to the environment.
European List of Waste (LoW) code	: 08 05 01* - waste isocyanates 15 01 02 - plastic packaging

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number		
Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name		
Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)		
Not applicable	Not applicable	Not applicable
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Not applicable	Not applicable	Not applicable
No additional information available		

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

2K Rapido (50ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Air transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 0 g/l

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

A chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH204	Contains isocyanates. May produce an allergic reaction.

2K Rapido (50ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.