

SAFETY DATA SHEET
FOOD GRADE POWER LUBE

Page: 1

Compilation date: 22-09-2014

Revision date: 13-03-2018

Revision No: 33

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FOOD GRADE POWER LUBE

Product code: 1007

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC24: Lubricants, greases, release products.

1.3. Details of the supplier of the safety data sheet

Company name: ProPart International B.V.

Molenakker 3

Reuver

5953 TW

The Netherlands

Tel: +31 (0) 77 476 2368

Fax: +31 (0) 77 476 2424

Email: info@propart-international.com

1.4. Emergency telephone number

Emergency tel: +31 (0) 77 476 2368 (08.30-17.00)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H336; Aquatic Chronic 3: H412; Flam. Aerosol 1: H222; -: H229; -: EUH066

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

EUH066: Repeated exposure may cause skin dryness or cracking.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



[cont...]

SAFETY DATA SHEET
FOOD GRADE POWER LUBE

Page: 2

Signal words: Danger

Precautionary statements: P501: Dispose of contents/container to waste according to local/regional/national/international regulations.
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P103: Read label before use.
P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251: Do not pierce or burn, even after use.
P211: Do not spray on an open flame or other ignition source.
P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PENTANE - REACH registered number(s): 01-2119459286-30-XXXX

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|-----------|----------|-----------|--|---------|
| 203-692-4 | 109-66-0 | - | Flam. Liq. 2: H225; Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411; -: EUH066 | 10-30% |

PROPANE - REACH registered number(s): 01-2119486944-21-XXXX

| | | | | |
|-----------|---------|--|-------------------------------------|--------|
| 200-827-9 | 74-98-6 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 10-30% |
|-----------|---------|--|-------------------------------------|--------|

BUTANE - REACH registered number(s): 01-2119474691-32-XXXX

| | | | | |
|-----------|----------|--|-------------------------------------|--------|
| 203-448-7 | 106-97-8 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 10-30% |
|-----------|----------|--|-------------------------------------|--------|

ISOBUTANE (CONTAINS <0,1% BUTADIENE (203-450-8)) - REACH registered number(s): 01-2119485395-27-XXXX

| | | | | |
|-----------|---------|--|-------------------------------------|-------|
| 200-857-2 | 75-28-5 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 1-10% |
|-----------|---------|--|-------------------------------------|-------|

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.
Eye contact: Bathe the eye with running water for 15 minutes. If irritation persists, consult a doctor.
Ingestion: Drink plenty of water and provide fresh air. Call a doctor immediately.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

[cont...]

SAFETY DATA SHEET
FOOD GRADE POWER LUBE

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers. Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant foam. Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

[cont...]

SAFETY DATA SHEET
FOOD GRADE POWER LUBE

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Do not handle in a confined space. Avoid the formation or spread of mists in the air.
Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed. Keep away from direct sunlight. Prevent the build up of electrostatic charge in the immediate area. The floor of the storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PENTANE

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|-------|------------------------|--------------|------------|--------------|
| UK | 1800 mg/m ³ | - | - | - |

PROPANE

| | | | | |
|----|------------------------|------------------------|---|---|
| UK | 1800 mg/m ³ | 7200 mg/m ³ | - | - |
|----|------------------------|------------------------|---|---|

BUTANE

| | | | | |
|----|------------------------|------------------------|---|---|
| UK | 1450 mg/m ³ | 1810 mg/m ³ | - | - |
|----|------------------------|------------------------|---|---|

ISOBUTANE (CONTAINS <0,1% BUTADIENE (203-450-8))

| | | | | |
|----|------------------------|------------------------|---|---|
| UK | 2400 mg/m ³ | 9600 mg/m ³ | - | - |
|----|------------------------|------------------------|---|---|

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Not applicable.

Eye protection: Not applicable.

Skin protection: Not applicable.

SAFETY DATA SHEET
FOOD GRADE POWER LUBE

Page: 6

Hazardous ingredients:

PENTANE

| | | | | |
|-----|-----|------|-----|-------|
| IVN | MUS | LD50 | 446 | mg/kg |
| ORL | RAT | LD50 | 400 | mg/kg |

Relevant hazards for product:

| Hazard | Route | Basis |
|----------------------|-------|-----------------------|
| STOT-single exposure | - | Hazardous: calculated |

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

| Species | Test | Value | Units |
|---------------|----------|-------|-------|
| CAS 109-66-0 | - | - | - |
| Daphnia magna | 48H EC50 | 9,7 | mg/l |
| FISH | 96H LC50 | 1-10 | mg/l |

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Water hazard class (NL) 8: Harmful to aquatic organisms; may cause long-term adverse effects in the aquatic environment. Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

[cont...]

SAFETY DATA SHEET
FOOD GRADE POWER LUBE

Page: 7

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company. Must not be disposed together with household garbage or into the sewage system.

Waste code number: 20 01 13

Disposal of packaging: Uncontaminated packaging can be recycled.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: Warning: Gases. EMS number:F-D,S-U.

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

[cont...]

SAFETY DATA SHEET
FOOD GRADE POWER LUBE

Page: 8

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.
H220: Extremely flammable gas.
H222: Extremely flammable aerosol.
H225: Highly flammable liquid and vapour.
H229: Pressurised container: May burst if heated
H280: Contains gas under pressure; may explode if heated.
H304: May be fatal if swallowed and enters airways.
H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.