

RUST-EX SPRAY

Page: 1

Compilation date: 18-09-2014

Revision date: 17-03-2014

Revision No: 6

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: RUST-EX SPRAY

Product code: 1200

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC14: Metal surface treatment products, including galvanic and electroplating products.

1.3. Details of the supplier of the safety data sheet

Company name: ProPart International B.V.

Molenakker 3

Reuver 5953 TW

The Netherlands

Tel: +31 (0) 77 476 2368 **Fax:** +31 (0) 77 476 2424

Email: info@propart-international.com

1.4. Emergency telephone number

Emergency tel: +31 (0) 77 476 2368 (08.30-17.00)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F+: R12; -: R52/53; -: R66; -: R67

Classification under CLP: Flam. Aerosol 1: H222; Eye Irrit. 2: H319; Aquatic Chronic 3: H412; -: H229; -: EUH066

Most important adverse effects: Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse

effects in the aquatic environment. Repeated exposure may cause skin dryness or

cracking. Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements under CLP:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

EUH066: Repeated exposure may cause skin dryness or cracking.

Signal words: Danger

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark

[cont...]

RUST-EX SPRAY

Page: 2





Precautionary statements: P501: Dispose of contents/container to waste according to

local/regional/national/international regulations.

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251: Pressurized container: Do not pierce or burn, even after use.

P211: Do not spray on an open flame or other ignition source.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Label elements under CHIP:

Hazard symbols: Extremely flammable.



Risk phrases: R12: Extremely flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S38: In case of insufficient ventilation, wear suitable respiratory equipment.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures

exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources

of ignition - No smoking. Keep out of the reach of children.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ACETONE

EINECS C	AS CHIP Classification	CLP Classification	Percent
----------	------------------------	--------------------	---------

RUST-EX SPRAY

Page: 3

200-662-2	67-64-1	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	16.250%
PENTANE				
203-692-4	109-66-0	F+: R12; N: R51/53; Xn: R65; -: R66; -: R67	Flam. Liq. 2: H225; Asp. Tox. 1: H304; STOT SE 3: H336; Aquatic Chronic 2: H411; -: EUH066	16.250%
LOW BOILING	G POINT HYDRO	OGEN TREATED NAPHTHA - NAPH	THA (PETROLEUM), HYDRODESULPHUR	IZED
265-185-4	64742-82-1	Xn: R65; -: R10; N: R51/53	Asp. Tox. 1: H304; Flam. Liq. 3: H226; Aquatic Chronic 2: H411	11.250%
1-METHOXY-	2-PROPANOL			
203-539-1	107-98-2	-: R10; -: R67 Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226; STOT SE 3: H336	3.750%

Non-classified ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

EINECS	CAS	CHIP Classification	CLP Classification	Percent		
265-150-3	64742-48-9	Xn: R65; -: R10; -: R66	Asp. Tox. 1: H304; Flam. Liq. 3: H226	37.500%		
KOOLSTOFDIOXIDE						
204-696-9	124-38-9	-	-	0.550%		

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Bij aanhoudende irritatie een arts

raadplegen. If irritation persists, consult a doctor. Bei anhaltender Reizung einen Arzt

konsultieren. Si l'irritation persiste, consulter un médecin.

Ingestion: Drink plenty of water and provide fresh air. Drink zeer veel water en voer verse lucht aan.

Buvez beaucoup d'eau et de l'air frais. Trinken Sie viel Wasser und Frischluftzufuhr. Call

a doctor immediately. Onmiddellijk een dokter waarschuwen. Appelez un docteur

immédiatement. Rufen Sie sofort einen Arzt an.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

RUST-EX SPRAY

Page: 4

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers. Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant

foam. Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of

ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container

tightly closed. Keep away from direct sunlight. Prevent the build up of electrostatic

RUST-EX SPRAY

Page: 5

charge in the immediate area. The floor of the storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ACETONE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1210 mg/m3	3620 mg/m3	-	-

PENTANE

UK 1800 mg/m3 - -	UK	1800 mg/m3	_	-	
-------------------------	----	------------	---	---	--

1-METHOXY-2-PROPANOL

UK 375 mg/m3 560 mg/m3	-
------------------------	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be

impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Not applicable.Eye protection: Not applicable.Skin protection: Not applicable.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: According to product specification.

Odour: Characteristic odour

Evaporation rate: Not applicable.

Solubility in water: Not / slightly miscible.

Viscosity: No data available.

Boiling point/range°C: Not applicable. **Melting point/range°C:** No data available.

Flammability limits %: lower: 0,6 upper: 13,0

Flash point°C: <0 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No autoignition

[cont...]

RUST-EX SPRAY

Page: 6

Vapour pressure: 5750 hPa

Relative density: No data available.

pH: No data available.

VOC g/I: 666,2 g/I - EU-VOC in%: 85,64%

9.2. Other information

Other information: Ignition temperature: 240°C. Density: 0,778 g/cm3 (20°C). Solvent content: organic

solvent: 85,6%.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

PENTANE

IVN	MUS	LD50	446	mg/kg
ORL	RAT	LD50	400	mg/kg

RUST-EX SPRAY

Page: 7

1-METHOXY-2-PROPANOL

IVN	RAT	LD50	4200	mg/kg
ORL	MUS	LD50	11700	mg/kg
ORL	RAT	LDLO	3739	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
CAS 64742-48-9	-	-	-
Crustacean amphipod	96H LC50	>100	mg/l
FISH	-	>100	mg/l
CAS 67-64-1	-	-	-
Daphnia magna	48H EC50	8800	mg/l
Daphnia magna	48H LC50	2262	mg/l
FISH	96H LC50	5540	mg/l
CAS 109-66-0	-	-	-

Hazardous ingredients:

ACETONE

BLUEGILL (Lepomis macrochirus)	LC50	8300	mg/l
--------------------------------	------	------	------

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

RUST-EX SPRAY

Page: 8

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Waterbezwaarlijkheid (NL) 8: Schadelijk voor in het water

levende organismen; kan in het aquatisch milieu op lange termijn schadelijke effecten veroorzaken. Gevaar voor water klasse 2 (D) (Zelfclassificatie): gevaar voor water.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company. Must not be disposed together with household garbage or into the sewage system. Mag niet tezamen met huisvuil gestort worden of in de riolering terechtkomen. Darf nicht zusammen mit Hausmüll entsorgt werden oder in die Kanalisation gelangen. Ne doit pas être évacué avec les ordures ménagères à pénétrer dans les canalisations.

Waste code number: 20 01 13

Disposal of packaging: Uncontaminated packaging can be recycled. Niet besmette verpakkingen kunnen een

recycling ondergaan. Pas les emballages contaminés peuvent être recyclés. Nicht

kontaminierte Verpackungen können recycelt werden.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: Warning: Gases. EMS number:F-D,S-U.

Tunnel code: D
Transport category: 2

RUST-EX SPRAY

Page: 9

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated

H304: May be fatal if swallowed and enters airways.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

R10: Flammable.

R11: Highly flammable.

R12: Extremely flammable.

R36: Irritating to eyes.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legend to abbreviations: PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

RUST-EX SPRAY

Page: 10

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.