

PLASTIC PRIMER SPRAY (400ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Date of issue: 5/3/2019 Revision date: 11/19/2018 Supersedes: 1/23/2018 Version: 54.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : PLASTIC PRIMER SPRAY (400ml)
Product code : 5050/TCAP
Vaporizer : Aerosol
Product group : Coatings and paints, thinners, paint removers

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Consumer use
Use of the substance/mixture : Consumer uses: Private households (= general public = consumers)
Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Function or use category : Industrial spraying, Non-industrial spraying

1.2.2. Uses advised against

Restrictions on use : No additional information available

1.3. Details of the supplier of the safety data sheet

ProPart International B.V.
Molenakker 3 3
5953 TW Reuver - Nederland
T +31 (0) 77 476 2368
info@propart-international.com - www.propart-international.com

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Extremely flammable liquid and vapour. May cause cancer. May cause genetic defects. May cause drowsiness or dizziness. Causes skin irritation.
Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP)

: Danger

PLASTIC PRIMER SPRAY (400ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H411 - Toxic to aquatic life with long lasting effects.
H220 - Extremely flammable gas.
H226 - Flammable liquid and vapour.
H312 - Harmful in contact with skin.
H332 - Harmful if inhaled.
H280 - Contains gas under pressure; may explode if heated.
H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H373 - May cause damage to organs (digestive tract) through prolonged or repeated exposure (if inhaled, if swallowed).
H412 - Harmful to aquatic life with long lasting effects.
H229 - Pressurised container: May burst if heated.

Precautionary statements (CLP)

: P260 - Do not breathe dusts or mists.
P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE	(EC-No.) 921-024-6 (REACH-no) 01-2119475514-35	50 - 75	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
dimethyl ether substance with a Community workplace exposure limit	(CAS-No.) 115-10-6 (EC-No.) 204-065-8 (EC Index-No.) 603-019-00-8 (REACH-no) 01-2119472128-37	25 - 50	Flam. Gas 1, H220 Press. Gas (Liq.), H280
xylene	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	5 - 10	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
XYLENE	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9	< 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Comments

: Note C
Classification according to Regulation (EC) No. 1272/2008 [CLP]
Applicable
Xylene
MIXTURE

Full text of H-statements: see section 16

PLASTIC PRIMER SPRAY (400ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If unconscious, place in the recovery position and seek medical advice.
First-aid measures after skin contact	: Wash immediately with plenty of soap and water. Rinse with plenty of water.
First-aid measures after eye contact	: Immediately rinse with water for a prolonged period while holding the eyelids wide open.
First-aid measures after ingestion	: Obtain emergency medical attention. Drink plenty of water. Move to fresh air.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : No additional data.

4.3. Indication of any immediate medical attention and special treatment needed

No additional data.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : carbon dioxide (CO₂), water, dry chemical powder. For a significant fire : high volume water jet. Alcohol-resistant foam.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : On heating or during combustion : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Wear recommended personal protective equipment. Self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Full face piece respirator. Complete protective clothing. Keep public away.
Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Complete protective clothing. Approved respirator.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : For further information refer to section 13.
Methods for cleaning up : Ensure that there is a suitable ventilation system.
Other information : For further information refer to section 13.

6.4. Reference to other sections

Conditions and measures related to information and behavioural advice to consumers. See Heading 7. For further information refer to section 8: "Exposure controls/personal protection". This mixture does not contain any substances to be mentioned according to ABNT NBR 14725. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Respiratory protective device with a gas filter. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Ensure good ventilation of the work station.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.
Storage conditions : Dispose in a safe manner in accordance with local/national regulations. Gases under pressure.
Information on mixed storage : Not necessary under the recommended storage and handling conditions.
Storage area : Adequate closed storage facilities (e.g. bulk storage tanks, intermediate bulk containers, drums) for VOC-containing raw materials. Store substance within a closed system. Category 2B.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

dimethyl ether (115-10-6)

EU	Local name	Dimethylether
----	------------	---------------

PLASTIC PRIMER SPRAY (400ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

dimethyl ether (115-10-6)

EU	IOELV TWA (mg/m³)	1920 mg/m³
EU	IOELV TWA (ppm)	1000 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Germany	TRGS 910 Acceptable concentration notes	
Netherlands	Local name	Dimethylether
Netherlands	Grenswaarde TGG 8H (mg/m³)	950 mg/m³
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	1500 mg/m³
Netherlands	Regulatory reference	Arbeidsomstandighedenregeling 2018

xylene (1330-20-7)

EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m³)	221 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	442 mg/m³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Germany	TRGS 910 Acceptable concentration notes	
Netherlands	Local name	Xyleen, o-, m-, p-isomeren
Netherlands	Grenswaarde TGG 8H (mg/m³)	210 mg/m³
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	442 mg/m³
Netherlands	Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Netherlands	Regulatory reference	Arbeidsomstandighedenregeling 2018

XYLENE (1330-20-7)

EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m³)	221 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	442 mg/m³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Germany	TRGS 910 Acceptable concentration notes	
Netherlands	Local name	Xyleen, o-, m-, p-isomeren
Netherlands	Grenswaarde TGG 8H (mg/m³)	210 mg/m³
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	442 mg/m³
Netherlands	Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.

PLASTIC PRIMER SPRAY (400ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

XYLENE (1330-20-7)

Netherlands

Regulatory reference

Arbeidsomstandighedenregeling 2018

8.2. Exposure controls

Appropriate engineering controls:

Keep away from food, drink and animal feedingstuffs. Take off immediately all contaminated clothing. Wash hands before breaks and after work. Do not breathe gas/fumes/vapour/spray. When handling product, avoid contact with skin and eyes.

Personal protective equipment:

Gloves.

Hand protection:

Impermeable protective gloves. Penetration time of glove material: The average penetration time of the various materials when used with this product is unknown. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves					

Eye protection:

Safety glasses. Not necessary under the recommended storage and handling conditions

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear breathing apparatus if exposed to vapours/dusts/aerosols. In case of repeated or prolonged exposure : Wear a self contained breathing apparatus

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Aerosol can.
Colour	: Colourless.
Odour	: Solvent.
Odour threshold	: No information available
pH	: No information available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No information available
Melting point	: Not applicable
Freezing point	: No information available
Boiling point	: Aerosol Not applicable
Flash point	: < 0 °C Aerosol Not applicable
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No information available
Flammability (solid, gas)	: No information available
Vapour pressure	: 4000 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No information available
Relative density of saturated gas/air mixture	: No information available
Density	: 0.71 g/cm ³ bij 20° C
Solubility	: Water: Practically not miscible Organic solvent:99 %
Log Pow	: No data available

PLASTIC PRIMER SPRAY (400ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Viscosity, kinematic	: No data available
Viscosity, dynamic	: No information available
Explosive properties	: The product is not explosive, but the formation of explosive vapor / air mixtures is possible.
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0.6 vol %
Upper explosive limit (UEL)	: 26.2 vol %

9.2. Other information

VOC content	: 701.1 g/l EU-VOC in % : 99,16% VOC (EG) : 699,9 g/l
-------------	---

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available.

10.2. Chemical stability

To our knowledge, the product does not present any particular risk, under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

No additional data.

10.5. Incompatible materials

No additional data.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

LD50 oral rat	> 5840 mg/kg
LD50 dermal rabbit	> 2920 mg/kg
LC50 inhalation rat (mg/l)	> 25.2 mg/l/4h

xylene (1330-20-7)

LD50 oral rat	3523 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (mg/l)	29 mg/l/4h

XYLENE (1330-20-7)

LD50 oral rat	3523 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 inhalation rat (mg/l)	29 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. pH: No information available
Serious eye damage/irritation	: Not classified pH: No information available
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

PLASTIC PRIMER SPRAY (400ml)

Vaporizer	Aerosol
-----------	---------

PLASTIC PRIMER SPRAY (400ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Ecology - water	: toxic for aquatic organisms. Hazardous to water (WGK 2). Do not discharge into drains or rivers. Do not discharge into drains. Danger of pollution of drinking water when product enters the soil. harmful to plankton. Waterbezwaarlijkheid. B2.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Toxic to aquatic life with long lasting effects.

PLASTIC PRIMER SPRAY (400ml)

Additional information	Highly toxic to fishes
------------------------	------------------------

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE

LC50 fish 1	11.4 mg/l
EC50 Daphnia 1	3 mg/l
EC50 72h algae (1)	30 - 100 mg/l

dimethyl ether (115-10-6)

LC50 fish 1	> 4000 mg/l
EC50 Daphnia 1	> 4000 ml/l
EC50 96h algae (1)	155 mg/l

xylene (1330-20-7)

LC50 fish 1	13.5 mg/l
EC50 Daphnia 1	7.4 mg/l

XYLENE (1330-20-7)

LC50 fish 1	13.5 mg/l
EC50 Daphnia 1	7.4 mg/l

12.2. Persistence and degradability

PLASTIC PRIMER SPRAY (400ml)

Persistence and degradability	No additional information available.
-------------------------------	--------------------------------------

12.3. Bioaccumulative potential

PLASTIC PRIMER SPRAY (400ml)

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

PLASTIC PRIMER SPRAY (400ml)

Ecology - soil	No additional information available.
----------------	--------------------------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other adverse effects	: No additional information available.
-----------------------	--

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Entrust the uncontaminated packaging to a licensed waste contractor. Do not dispose of with domestic waste. Do not discharge into drains.
Additional information	: Recycle or dispose of in compliance with current legislation.
European List of Waste (LoW) code	: 15 01 04 - metallic packaging 20 01 13* - solvents

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

PLASTIC PRIMER SPRAY (400ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1950	UN 1950	UN UN1950	UN 1950	UN 1950
14.2. UN proper shipping name				
1950 Aerosols, environmentally hazardous	AEROSOLS	AEROSOLS, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 1950 Aerosols, environmentally hazardous, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN UN1950 AEROSOLS, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available				

14.6. Special precautions for user

Special transport precautions : Aerosol warning

Overland transport

Classification code (ADR) : 5F
 Limited quantities (ADR) : 1I
 Excepted quantities (ADR) : E0
 Transport category (ADR) : 2
 Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959
 Packing instructions (IMDG) : P207, LP200
 Special packing provisions (IMDG) : PP87, L2
 EmS-No. (Fire) : F-D
 EmS-No. (Spillage) : S-U
 Stowage category (IMDG) : None
 Stowage and handling (IMDG) : SW1, SW22
 Segregation (IMDG) : SG69

Air transport

No data available

Inland waterway transport

Classification code (ADN) : 5F
 Special provisions (ADN) : 190, 327, 344, 625
 Limited quantities (ADN) : 1 L
 Excepted quantities (ADN) : E0
 Equipment required (ADN) : PP, EX, A
 Ventilation (ADN) : VE01, VE04
 Number of blue cones/lights (ADN) : 1

PLASTIC PRIMER SPRAY (400ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

IBC code	: Not applicable.
----------	-------------------

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	PLASTIC PRIMER SPRAY (400ml) - xylene
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	PLASTIC PRIMER SPRAY (400ml)
3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	xylene
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	PLASTIC PRIMER SPRAY (400ml) - xylene

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

VOC content : 701.1 g/l EU-VOC in % : 99,16% VOC (EG) : 699,9 g/l

15.1.2. National regulations

Netherlands

SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: xylene,XYLENE are listed

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

PLASTIC PRIMER SPRAY (400ml)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.