

# FOOD GRADE POWER LUBE

LUBRICATION AND MAINTENANCE

- **Very good adhesion**
- **High viscosity**
- **Contains PTFE (Polytetrafluoroethylene)**
- **Weather resistant**

## PRODUCT DESCRIPTION :

High quality spray grease with PTFE for treatment of mechanical parts made of metal and plastics. Due the high viscosity, suitable for lubricating of highly targeted parts, which are subjected to high pressure. The unique formula makes it suitable for use in the food industry.

Corresponding NSF registration H1.

## APPLICATIONS :

- Metal to metal connections
- Metal to plastic connections
- Hinges of doors
- Bearings
- Springs
- Stabilization rubbers
- Worm wheels
- Conveyors

## INSTRUCTIONS :

For use, read and follow the instructions on the package carefully. Bring the aerosol to room temperature. Ideal processing temperature 5 to 30°C.

Shake before use. Apply Food Grade power lube in a thin layer.



**SPECIFICATIONS :**

<b>Content:</b>	500 ml
<b>Base:</b>	Mineral Oil and Fat EP
<b>VOS-content:</b>	Circa 71% w/w
<b>Colour:</b>	Beige
<b>Odour:</b>	Characteristic
<b>Appearance:</b>	Fat
<b>Density at 20°C:</b>	0,76 gr/ml
<b>Spray proceeds:</b>	1,5 gr/sec.
<b>Vapour pressure at 20°C:</b>	3 until 4 bar
<b>4 Ball EP-test (ASTM D 2596):</b>	3136 N
<b>4 Ball Wear-test (ASTM D 2266):</b>	< 0,4 mm
<b>Temperature resistant:</b>	-30°C to +160°C
<b>pH-value:</b>	Neutral